

Appendix I
MSDS Forms

Material Safety Data Sheet

Leaded gasoline



1. Product and company identification

Product name : Leaded gasoline
Material uses : Fuel.
Manufacturer / Supplier : VP Racing Fuels, Inc
Formulations Department
7124 Richter Road
Elmendorf, Texas 78112
1-210-635-7744
Validation date : 4/26/2007.
Print date : 4/26/2007.
In case of emergency : 1 (800) 424-9300
Outside the US: +1 703-527-3887 (CHEMTREC)
Product type : Liquid.

2. Hazards identification

Physical state : Liquid.
Odor : Characteristic.
OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Emergency overview : WARNING !
FLAMMABLE LIQUID AND VAPOR. INHALATION CAUSES HEADACHES, DIZZINESS, DROWSINESS AND NAUSEA AND MAY LEAD TO UNCONSCIOUSNESS. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION. HARMFUL OR FATAL IF SWALLOWED. CAN ENTER LUNGS AND CAUSE DAMAGE. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE. SUSPECT CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER.
Flammable liquid. Defatting to the skin. May cause skin dryness and irritation. Aspiration hazard if swallowed. Can enter lungs and cause damage. Keep away from heat, sparks and flame. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Contains material that can cause target organ damage. Contains material which may cause cancer. Risk of cancer depends on duration and level of exposure. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Routes of entry : Inhalation; Skin contact; Ingestion
Potential acute health effects
Inhalation : Can cause central nervous system (CNS) depression.
Ingestion : Can cause central nervous system (CNS) depression. Aspiration hazard if swallowed. Can enter lungs and cause damage.
Skin : May cause skin dryness and irritation.
Eyes : May cause eye irritation.
Potential chronic health effects
Chronic effects : Contains material that can cause target organ damage. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Carcinogenicity : Contains material which may cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.

4/26/2007.

1/10

2. Hazards identification

- Developmental effects** : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.
Target organs : Contains material which causes damage to the following organs: kidneys, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
- Skin** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Eyes** : No specific data.
- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
complex combination of hydrocarbons	8006-61-9	99.9
motorfuel antiknock compound	78-00-2	<1

4. First aid measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Get medical attention immediately. Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Get medical attention immediately. Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

4 . First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing or wear gloves.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 . Fire-fighting measures

- Flammability of the product** : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

- Suitable** : Use dry chemical, CO₂, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous combustion products** : No specific data.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on fire hazards** : Not available.
- Special remarks on explosion hazards** : Not available.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flames, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

<u>Product name</u>	<u>Exposure limits</u>
complex combination of hydrocarbons	<p>OSHA PEL 1989 (United States, 3/1989). STEL: 1500 mg/m³ 15 minute(s). STEL: 500 ppm 15 minute(s). TWA: 900 mg/m³ 8 hour(s). TWA: 300 ppm 8 hour(s).</p>
motorfuel antiknock compound	<p>ACGIH TLV (United States, 1/2006). Skin Notes: as Pb 1996 Adoption Substances for which the TLV is higher than the OSHA Permissible Exposure Limit (PEL) and/or the NIOSH Recommended Exposure Limit (REL). See CFR 58(124) :36338-33351, June 30, 1993, for revised OSHA PEL. Refers to Appendix A - - Carcinogens. For greater assurance of worker protection, biological monitoring is recommended. TWA: 0.1 mg/m³, (as Pb) 8 hour(s). NIOSH REL (United States, 12/2001). Skin Notes: as Pb TWA: 0.075 mg/m³, (as Pb) 10 hour(s). OSHA PEL (United States, 8/1997). Skin Notes: as Pb TWA: 0.075 mg/m³, (as Pb) 8 hour(s). OSHA PEL 1989 (United States, 3/1989). Skin Notes: as Pb TWA: 0.08 mg/m³, (as Pb) 8 hour(s).</p>

Consult local authorities for acceptable exposure limits.

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
- Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

8 . Exposure controls/personal protection

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Personal protective equipment (Pictograms)



9 . Physical and chemical properties

Physical state : Liquid.
Flash point : Not available.
Auto-ignition temperature : Not available.
Flammable limits : Not available.
Color : Various
Odor : Characteristic.
pH : Not available.
Boiling/condensation point : Not available.
Melting/freezing point : -62°C (-79.6°F)
Relative density : 0.625 to 0.88
Vapor pressure : <151.6 kPa (<1137 mm Hg)
Vapor density : Not available.
Odor threshold : Not available.
Evaporation rate : Not available.
Viscosity : Kinematic (40°C): 0.009 cm²/s (0.9 cSt)
Octanol/water partition coefficient : Not available.

10 . Stability and reactivity

- Stability** : The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Avoid exposure - obtain special instructions before use. Do not swallow.
- Materials to avoid** : Reactive or incompatible with the following materials: oxidizing materials
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Conditions of reactivity** : Not available.

11 . Toxicological information

United States

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
motorfuel antiknock compound	LD50 Intraperitoneal	Rat	15 mg/kg	-
	LD50 Intravenous	Rat	14400 ug/kg	-
	LD50 Oral	Rat	12300 ug/kg	-
	LD50 Parenteral	Rat	15 mg/kg	-

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
complex combination of hydrocarbons	-	2B	-	-	-	-
motorfuel antiknock compound	A4	3	-	-	Possible	-

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Synergistic products : Not available.

12 . Ecological information

Environmental effects : No known significant effects or critical hazards.

United States

Aquatic ecotoxicity

Conclusion/Summary : Not available.

Biodegradability

Conclusion/Summary : Not available.

Other adverse effects : No known significant effects or critical hazards.







13 . Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	1268	PETROLEUM DISTILLATES, N.O.S.	3	II		
TDG Classification	1268	PETROLEUM DISTILLATES, N.O.S.	3	II		-
Mexico Classification	1268	PETROLEUM DISTILLATES, N.O.S.	3	II		-
ADR/RID Class	1268	PETROLEUM DISTILLATES, N.O.S.	3	II		-
IMDG Class	1268	PETROLEUM DISTILLATES, N.O.S.	3	II		-
IATA-DGR Class	1268	PETROLEUM DISTILLATES, N.O.S.	3	II		-

PG* : Packing group

15 . Regulatory information

United States

HCS Classification : Flammable liquid
Irritating material
Carcinogen
Target organ effects

U.S. Federal regulations : **United States inventory (TSCA 8b)**: All components are listed or exempted.
SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: complex combination of hydrocarbons
SARA 311/312 MSDS distribution - chemical inventory - hazard identification: complex combination of hydrocarbons: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard

15 . Regulatory information

Clean Water Act (CWA) 307: motorfuel antiknock compound
 Clean Water Act (CWA) 311: motorfuel antiknock compound
 Clean Air Act (CAA) 112 accidental release prevention: No products were found.
 Clean Air Act (CAA) 112 regulated flammable substances: No products were found.
 Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

State regulations : **Massachusetts Substances**: The following components are listed: GASOLINE
New Jersey Hazardous Substances: The following components are listed:
 GASOLINE;TETRAETHYL LEAD
Pennsylvania RTK Hazardous Substances: The following components are listed:
 PLUMBANE, TETRAETHYL-

California Prop. 65

WARNING: This product contains a chemical or chemicals known to the state of California to cause birth defects (or other reproductive harm). Avoid breathing exhaust fumes and vapors. Do not use products in an indoor facility or in any facility without adequate ventilation.

<u>Ingredient name</u>	<u>Cancer</u>	<u>Reproductive</u>	<u>No significant risk level</u>	<u>Maximum acceptable dosage level</u>
complex combination of hydrocarbons	Yes.	Yes.	No.	No.
motorfuel antiknock compound	Yes.	No.	No.	No.

United States inventory (TSCA 8b) : **United States inventory (TSCA 8b)**: All components are listed or exempted.

Canada

WHMIS (Canada) : Class B-2: Flammable liquid
 Class D-1A: Material causing immediate and serious toxic effects (Very toxic).
 Class D-2A: Material causing other toxic effects (Very toxic).


Canadian lists : **CEPA Toxic substances**: None of the components are listed.
Canadian ARET: None of the components are listed.
Canadian NPRI: None of the components are listed.
Alberta Designated Substances: None of the components are listed.
Ontario Designated Substances: None of the components are listed.
Quebec Designated Substances: None of the components are listed.

Canada inventory : **Canada inventory**: All components are listed or exempted.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

Mexico

Classification :



EU regulations

Hazard symbol or symbols :

The image shows two EU hazard symbols side-by-side. The left symbol is a flame, representing a flammable hazard (F+). The right symbol is a skull and crossbones, representing a toxic hazard (T+).

15 . Regulatory information

- Risk phrases** : R11- Highly flammable.
 R45- May cause cancer.
 R61- May cause harm to the unborn child.
 R26/27/28- Very toxic by inhalation, in contact with skin and if swallowed.
 R65- Harmful: may cause lung damage if swallowed.
 R33- Danger of cumulative effects.
 R52/53- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Safety phrases** : S53- Avoid exposure - obtain special instructions before use.
 S28- After contact with skin, wash immediately with plenty of water.
 S36/37- Wear suitable protective clothing and gloves.
 S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

International regulations

- International lists** : **Australia inventory (AICS)**: All components are listed or exempted.
China inventory (IECSC): All components are listed or exempted.
Korea inventory (KECI): All components are listed or exempted.
Philippines inventory (PICCS): All components are listed or exempted.
Japan inventory (ENCS): Not determined.

16 . Other information


Hazardous Material Information System (U.S.A.) :

Health	*	2
Flammability		4
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) :



- Date of printing** : 4/26/2007.
Date of issue : 4/26/2007.
Date of previous issue : 3/30/2007.
Version : 1

☑ Indicates information that has changed from previously issued version.

Notice to reader

Leaded gasoline

16 . Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

VHT Quality Finish Coatings

VHT Quick Coat

VHT Quick-Coat Polyurethane Enamel is a premium quality coating which provides extra hide and durability for interior or exterior applications. This tough and durable coating prevents rust, corrosion on properly prepared surfaces, is fast drying, lead free and ozone safe.

VHT Quick-Coat Polyurethane Enamel provides a rich weather resistant gloss finish to wood, metal, sealed plaster and masonry surfaces.

16OZ CANS

SP-501	FIRE RED	\$7.70
SP-503	BRIGHT ORANGE	\$7.70
SP-504	GLOSS BLACK	\$7.70
SP-505	OCEAN BLUE	\$7.70
SP-507	BRIGHT ALUMINUM	\$7.70
SP-508	BRIGHT YELLOW	\$7.70
SP-509	GLOSS WHITE	\$7.70
SP-510	FLAT BLACK	\$7.70
SP-511	FLAT WHITE	\$7.70
SP-512	FOREST GREEN	\$7.70
SP-513	MACHINERY GRAY	\$7.70
SP-514	GOLD	\$7.70
SP-515	CLEAR	\$7.70
SP-519	DARK BLUE	\$7.70
SP-525	SILVER CHROME	\$7.70
SP-526	DARK BROWN	\$7.70



ALL VHT PRODUCTS ARE
ORM-D



VHT Epoxy Paint

VHT Epoxy Paint - All Weather contains a one-step Epoxy Ester resin which dries in minutes to provide an exceptional rust and corrosion resistant finish. The rust inhibitors which are added to this already fortified resin produce a rust proof barrier when applied to new or properly prepared metal substrates.

VHT Epoxy Paint - All Weather is tough enough for industrial use yet safe enough for children's toys. Can be used Interior or Exterior, no primer required.

16OZ CANS

SP-650	GLOSS BLACK	\$8.25
SP-651	GLOSS WHITE	\$8.25
SP-652	SATIN BLACK	\$8.25
SP-654	FIRE RED	\$8.25
SP-656	STAINLESS STEEL	\$8.25



VHT Track Bite

VHT TrackBite sets faster, stays tacky for weeks and will not run off even in heavy rains.

This original competition formula will increase race competition and times better than any other track treatment available.

VHT TrackBite was applied to the track surface at every NHRA & IHRA race when world drag strip records were set over the past decade.

*VHT TrackBite contains no petroleum distillate, will not soften track or adversely effect tire performance or life.

VHT TRACKBITE SP-162 is an exclusive consumer formulation designed to offer controlled traction for competition drag racing. VHT TrackBite is a liquid track treatment, which improves traction by means of adhesion and does not soften tires nor the track surface as other imitation products may. SP-162 is packaged in a one gallon bottle.

VHT TrackBite SP-163, Drag Strip Formula, 55 Gallon Drum is a high solids, quick setting liquid track treatment designed specifically for drag track racing competition.

This exclusive formulation is designed to offer controlled traction, quicker times and create more exciting racing.

VHT TRACKBITE CONCENTRATE, SP-165 has been engineered for paved oval tracks. Also packaged in 54 gallon drums, this formula is designed to withstand the rigors of extreme cornering loads, while enhancing side bite. Very durable, will not harm track surface or tires as other imitation products may, and will withstand extreme exposure to the sun's heat. VHT TrackBite Concentrate, SP-165 is also an excellent sealer on freshly ground and/or resurfaced tracks. Used at leading USAC and NASCAR sanctioned paved ovals. VHT TrackBite has been used by every major drag strip and drag racing sanctioning body since 1972.

SP-162

TRACKBITE

1 GAL

\$29.99